

PTF Maschinenhandelsges. mbH
Kreuzsteig 6
72479 Strassberg
Phone: +49 (0)7574 93 622 83
Email: info@ptf-maschinen.de
Web: www.ptf-maschinen.de



Machine datasheet

stock no.: 1107-3202



Machine type: Deburring and edge rounding machine
Manufacturer: Lissmac
Type: SBM-S 1500
Serial no.:
YOM: 2006
delivery time: immediately
Location: 72479 Strassberg



technical details:

max. working width:	1500 mm
workable material thickness:	20 mm
Tension:	400 V / 50 Hz
Total power:	28,5 A
Total current consumption:	12,6 kW
Insulation class:	IP54
Infinitely variable feed speed:	0-4 m / min
Length:	2730 mm
Width:	1500 mm
Height:	1532 mm
Machine weight:	2200 kg

Standard configuration:

- adjustment of material thickness: fully variable / manual
- adjustment of tools: fully variable / manual

Extended machine accessories:

TEKA Filtercube 2N (2011)

Automation:

- infeed and outfeed belt

Description:

Lissmac innovative systems for metal processing set high standards for metal finishing. Their unique method of simultaneously deburring edges on inside and outside contours of steel, stainless steel, or laser cut parts on both sides in one single pass is highly efficient. Compared to conventional deburring machines Lissmac saves processing times of up to 60%.

Features and Benefits - Deburring machine SBM-S

- Deburring and edge rounding of sheet and plate up to 20 mm material thickness
- No need to turn sheets over and running them through the machine again
- Highest quality during subsequent processing or finishing
- Simultaneous processing of all inside and outside edges
- Even and slow wear of consumables
- No damage to the parent metal - tolerances remain intact
- Will even deburr sheet covered in protective film without damaging the film
- Belt surface equal to 7,5 sq m of abrasive material - few tool changes
- Dry operation - no water, sludge or complex drying process
- Infinitely variable feed speed
- Easy and safe operation with minimal maintenance
- Compact and modular construction - less space needed
- The operation of all Lissmac grinding, deburring, and edge rounding machines can be linked and sequenced together with innovative conveyor systems and combined single controls